



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF6262-30A	262mm	DAYLIGHT WHITE	850	350	5 ± 1	3,000	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
			DRAWN BY L. WENGSTROM		APPV'D BY DATE JK 11/27/00		TITLE DUAL LEAD TIP TYPE DAYLIGHT WHITE MINIATURE FLUORESCENT LAMP				
RELEASED			11/27/00		SCALE A		FSCM NO. 55335		DRAWING NO. BF 6-30A		
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED				SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
							NONE	11/27/00			1 OF 1