



preci-dip

## SURFACE MOUNT SPRING LOADED CONTACTS

PART NUMBER	ABOVE BOARD HEIGHT		STROKE DISTANCE		INITIAL FORCE	<sup>1</sup> / <sub>2</sub> STROKE FORCE
	mm	inch	mm	inch	Newton	Newton
90173-AS	2.55	0.100	0.6	0.024	0.4	0.85
90174-AS	2.7	0.106	0.75	0.030	0.4	0.85
90123-AS	2.78	0.109	0.6	0.024	0.6	0.8
90041-AS	3.5	0.138	1	0.039	0.45	0.85
90022-AS	4.25	0.167	1.4	0.055	0.25	0.6
90023-AS	4.5	0.177	1.4	0.055	0.25	0.6
90024-AS	5	0.197	1.4	0.055	0.25	0.6
90025-AS	5.5	0.217	1.4	0.055	0.25	0.6
90026-AS	6	0.236	1.4	0.055	0.25	0.6
90093-AS	6	0.236	1.2	0.047	0.2	0.9
90150-AS	6	0.236	1.4	0.055	0.25	0.85
90233-AS	6	0.236	1.8	0.071	0.2	0.7
90027-AS	6.5	0.256	1.4	0.055	0.2	0.6
90151-AS	6.5	0.256	1.4	0.055	0.2	0.85
90235-AS	6.6	0.260	2	0.079	0.2	0.9
90028-AS	7	0.276	1.4	0.055	0.25	0.6
90152-AS	7	0.276	1.4	0.055	0.25	0.85
90029-AS	7.5	0.295	1.4	0.055	0.25	0.6
90153-AS	7.5	0.295	1.4	0.055	0.25	0.65
90013-AS	8.2	0.323	2.2	0.087	0.2	0.3
90089-AS	8.2	0.323	2.2	0.087	0.4	1.3
90203-AS	8.2	0.323	1.8	0.071	0.5	1.05
90234-AS	8.5	0.335	2	0.079	0.25	0.9
90245-AS	9.4	0.370	2	0.079	0.25	0.65

